



Double Girder Crane Type ZLK7

Notes:

1. Runway electrification is standard on left side.
2. Wheel loads do not include impact.
3. Shipping weights include hoist and trolley.

WHEEL LOADS INDICATED WITHOUT IMPACT OR WALKWAY

Cap. Tons	Hoist			Trolley			Endtruck				Bridge							Wheel Load Lbs.	Shipping Weight Lbs.	
	Type Reeving Rope Dia.	Speed FPM HP	Lift Ft.	Type Weight	HP per Motor 80/20 VFD	TRC In.*	Wheel			HP per Motor 120 VFD	Span Ft.	L1 In.	L2 In.	C1 In.	A1 In.	K1 In.	Z In.			
							Dia. In.	Base Ft.-In.	Length Ft.-In.											
30	5300 6/1 0.625	10.5/1.6 20.4/3.4	13	EM5300L6 091.61.040 4450 lbs.	2 x 0.75	78.75	10	8'-10"	10'-6"	2x2.0	24	46	46	7	10	55	8	30268	17539	
						78.75					28							31134	18624	
						78.75					32							32100	20012	
						78.75					36							32918	21275	
						78.75					40							33724	22897	
						78.75					44							34494	24769	
			78.75	48	35035	25876														
			78.75	52	35734	28522														
			78.75	56	36340	30270														
			78.75	60	36904	31959														
			78.75	64	37462	33588														
			78.75	68	38238	35176														
	78.75	72	39129	41598																
	78.75	76	39660	43519																
	78.75	80	41072	46831																
	78.75	84	41924	49851																
	78.75	88	42199	52513																
	98.5	92	42480	53716																
	98.5	96	43530	57566																
	98.5	100	44623	61596																
	33*	EM5300H6 091.61.110 5200 lbs.					16	12'-6"	15'-0"	2x5.0	78.75							41072	46831	
											78.75							36	41924	49851
											78.75							36	42199	52513
											78.75							36	42480	53716
98.5											38							43530	57566	
98.5											38							44623	61596	