



Note: See last page of DLVM section for drawing of low headroom EDL under running style.

Single Girder Under Running Crane Type DLVM4

DL	E min	E1	LA	M6	M7	N min	RF	T
5.13	3.25	1	20	10	8.75	8.75	8.25	1.13

Max. U1/U2 = 20"

Cap. Tons	Hoist		Lift Ft.	Trolley		Endtruck			Bridge					Corner Load F Lbs.	Shipping Weight Lbs.																
	Type Reeving Rope Dia.	Speed FPM		Type Weight	HP per Motor 65/16 FPM	Wheel Dia. In.	Base Ft.-In.	Length Ft.-In.	HP per Motor 120 VFPM	Span Ft.	U1/U2	L1 In.	L2 In.			A1 In.	C1 In.	K1 In.													
		HP																													
5	1050 4/1 0.4	16/2.6 7.86/1.26	20	EM1050L 162.41.060 775 Lbs. .59/.144	5.125	5'-0"	6'-6"	2x0.75	20	14	3	10	26	46	6460	4865															
															28	46	6620	5215													
															32	48	6710	5915													
															36	48	6925	6575													
															40	48	7110	7395													
															44	48	7340	8435													
	33			33	EM1050L 162.41.100 835 Lbs.	5.125	6'-6"	8'-0"	2x0.75	20	14	3	10	28	51	7655	9055														
																31	51	7930	10475												
																31	51	8260	12055												
							7'-6"	9'-0"										5.125	7'-6"	9'-0"	2x0.75	20	14	3	10	31	51	8260	12055		
																												31	51	8260	12055
																												34	54	8820	13655