



Note: See last page of DLVM section for drawing of low headroom EDL under running style.

DL	E min	E1	LA	M6	M7	N min	RF	T
5.13	3.25	1	20	10	8.75	8.75	8.25	1.13
6.25	3.25	1	22	10	9	10.3	10.7	1.13

Max. U1/U2 = 20"

Single Girder Under Running Crane Type DLVM5

Cap. Tons	Hoist			Trolley		Endtruck				Bridge					Corner Load Lbs.	Shipping Weight Lbs.					
	Type Reeving	Speed FPM	Lift Ft.	Type	HP per Motor 65/16 FPM	Wheel		HP per Motor 120 VFPM	Span Ft.	U1/U2	L1 In.	L2 In.	A1 In.	C1 In.			K1 In.				
	Rope Dia.	HP	Ft.	Weight	Dia. In.	Base Ft.-In.	Length Ft.-In.											Dia. In.	Base Ft.-In.	Length Ft.-In.	A1 In.
7.5	2063 4/1 0.4	17/2.8 8.8/1.3	20	EM2063L 171.41.060 1200 Lbs.	.40/.10	5.125	5'-0"	6'-6"	2 x 0.75	20	23	10	26	49	10	8690	5600				
																28	51	10	8870	6050	
																28	51	10	9030	6900	
																28	51	10	9225	7300	
																28	51	10	9345	7800	
																31	54	10	9600	8580	
	33	EM2063L 171.41.100 1320 Lbs.	.40/.10	33	EM2063L 171.41.100 1320 Lbs.	.40/.10	6.25	6'-6"	8'-0"	2 x 1.0	20	23	10	34	57	12	9910	10400			
																	34	57	12	10265	11060
																	37	60	12	10670	12990
																	37	60	12	11065	14920
																	37	60	12	11065	14920
																	37	60	12	11065	14920