



Note: See last page of DLVM section for drawing of low headroom EDL under running style.

DL	E min	E1	LA	M6	M7	N min	RF	T
6.25	3.25	1.13	22	10	9	10.3	10.7	1.13

Max. U1/U2 = 20"

Single Girder Under Running Crane Type DLVM6

Cap. Tons	Hoist			Trolley		Endtruck			Bridge							Corner Load F Lbs.	Shipping Weight Lbs.	
	Type Reeving Rope Dia.	Speed FPM HP	Lift Ft.	Type Weight	HP per Motor 65/16 FPM	Wheel		HP per Motor 120 VFPM	Span Ft.	U1/U2	L1 In.	L2 In.	A1 In.	C1 In.	K1 In.			
						Dia. In.	Base Ft.-In.											Length Ft.-In.
10	3100 4/1 0.5	16/2.6	20	EM3100L 162.41.060 2150 Lbs.	.59/.14	6.25	5'-6"	6'-10"	2 x 1.0	24	20	23	10	28	51	12	12330	8940
										28				51	12500		9440	
										32				54	12700		10340	
										36				54	12990		10940	
										40				54	13150		11640	
										44				57	13490		12340	
	48	57	13670	13940														
	52	60	14060	15340														
	56	63	14470	16600														
	60	63	14990	19480														
								7'-6"	9'-0"									